




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>7</sup> :</b> <b>G06F 17/30</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 00/55766</b> <b>(43) International Publication Date:</b> 21 September 2000 (21.09.00)		
<table style="width: 100%; border: none;"> <tr> <td style="width: 45%; vertical-align: top; padding: 5px;"> <b>(21) International Application Number:</b> PCT/SE00/00482  <b>(22) International Filing Date:</b> 10 March 2000 (10.03.00)  <b>(30) Priority Data:</b>            9900894-8                      12 March 1999 (12.03.99)                      SE  <b>(71) Applicant (for all designated States except US):</b> QLIKTECH INTERNATIONAL AB [SE/SE]; Forskningsbyn Ideon, S-223 70 Lund (SE).  <b>(72) Inventor; and</b>  <b>(75) Inventor/Applicant (for US only):</b> WOLGÉ, Håkan [SE/SE]; Viborgsslingan 18, S-224 72 Lund (SE).  <b>(74) Agent:</b> AWAPATENT AB; P.O. Box 5117, S-200 71 Malmö (SE).         </td> <td style="width: 55%; vertical-align: top; padding: 5px;"> <b>(81) Designated States:</b> AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, DZ, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KR (Utility model), KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).   <b>Published</b>  <i>With international search report.</i>  <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> </td> </tr> </table>			<b>(21) International Application Number:</b> PCT/SE00/00482 <b>(22) International Filing Date:</b> 10 March 2000 (10.03.00) <b>(30) Priority Data:</b> 9900894-8                      12 March 1999 (12.03.99)                      SE <b>(71) Applicant (for all designated States except US):</b> QLIKTECH INTERNATIONAL AB [SE/SE]; Forskningsbyn Ideon, S-223 70 Lund (SE). <b>(72) Inventor; and</b> <b>(75) Inventor/Applicant (for US only):</b> WOLGÉ, Håkan [SE/SE]; Viborgsslingan 18, S-224 72 Lund (SE). <b>(74) Agent:</b> AWAPATENT AB; P.O. Box 5117, S-200 71 Malmö (SE).	<b>(81) Designated States:</b> AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, DZ, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KR (Utility model), KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
<b>(21) International Application Number:</b> PCT/SE00/00482 <b>(22) International Filing Date:</b> 10 March 2000 (10.03.00) <b>(30) Priority Data:</b> 9900894-8                      12 March 1999 (12.03.99)                      SE <b>(71) Applicant (for all designated States except US):</b> QLIKTECH INTERNATIONAL AB [SE/SE]; Forskningsbyn Ideon, S-223 70 Lund (SE). <b>(72) Inventor; and</b> <b>(75) Inventor/Applicant (for US only):</b> WOLGÉ, Håkan [SE/SE]; Viborgsslingan 18, S-224 72 Lund (SE). <b>(74) Agent:</b> AWAPATENT AB; P.O. Box 5117, S-200 71 Malmö (SE).	<b>(81) Designated States:</b> AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, DZ, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KR (Utility model), KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>			

**(54) Title:** METHOD FOR EXTRACTING INFORMATION FROM A DATABASE**(57) Abstract**

A method operates on a database to extract and present information to a user. The database comprises data tables containing values of a number of variables. The information is to be extracted by evaluating at least one mathematical function which operates on one or more selected calculation variables. The presented information is to be partitioned on one or more selected classification variables. The method comprises the steps of identifying all boundary tables; identifying all connecting tables; electing a starting table among said boundary and connecting tables; building a conversion structure that links values of each selected variable in the boundary tables to corresponding values of one or more connecting variables in the starting table; and evaluating the mathematical function for each data record of the starting table, by using the conversion structure, such that the evaluation yields a final data structure containing a result of the mathematical function for every unique value of each classification variable.



*FOR THE PURPOSES OF INFORMATION ONLY*

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

METHOD FOR EXTRACTING INFORMATION FROM A DATABASETechnical field

The present invention relates to a method for extracting information from a database. The database  
5 comprises a number of data tables containing values of a number of variables, each data table consisting of at least one data record including at least two of said values. The information is extracted by evaluation of at least one mathematical function, which operates on one or  
10 more selected calculation variables. Further, the extracted information is partitioned on one or more selected classification variables.

Background of the invention

It is often desired to extract specific information  
15 from a database that is stored on a secondary memory of a computer. More specifically, there is need to summarise a large amount of data in the database, and present the summarised data to a user in a lucid way. For example, a user might be interested in extracting total sales per  
20 year and client from a database including transaction data for a large company. Thus, the extraction involves evaluation of a mathematical function, e.g. a summation ("SUM(x\*y)"), operating on a combination of calculation variables (x, y), e.g. the number of sold items  
25 ("Number") and the price per item ("Price"). The extraction also involves partitioning the information according to classification variables, e.g. "Year" and "Client". Thus, the classification variables define how the result of the mathematical operation should be presented. In  
30 this specific case, the extraction of the total sales per year by client would involve evaluation of  
"SUM(Number\*Price) per Year, Client".

In one prior-art solution, a computer program is designed to process the database and to evaluate all

conceivable mathematical functions operating on all conceivable calculation variables partitioned on all conceivable classification variables, also called dimensions. The result of this operation is a large data structure commonly known as a multidimensional cube. This multidimensional cube is obtained through a very time-consuming operation, which typically is performed overnight. The cube contains the evaluated results of the mathematical functions for every unique combination of the occurring values of the classification variables. The user can then, in a different computer program operating on the multidimensional cube, explore the data of the database, for example by visualising selected data in pivot tables or graphically in 2D and 3D charts. When the user defines a mathematical function and one or more classification variables, all other classification variables are eliminated through a summation over the results stored in the cube for this mathematical function, the summation being made for all other classification variables. Thus, by adding or removing classification variables, the user can move up or down in the dimensions of the cube.

This approach has some undesired limitations. If the multidimensional cube after evaluation contains average quantities, e.g. the average sales partitioned on a number of classification variables, the user cannot eliminate one or more of these classification variables since a summation over average quantities does not yield a correct total average. In this case, the multidimensional cube must contain the average quantity split on every conceivable combination of classification variables as well, adding an extra complexity to the operation of building the multidimensional cube. The same problem arises for other quantities, e.g. median values.

Often it is difficult to predict all relevant mathematical functions, calculation variables and classification variables before making a first examination of the

data in the database. Upon identifying trends and patterns, the user might find a need to add a function or a variable to reach underlying details in the data. Then, the time-consuming procedure of building a new multi-  
5 dimensional cube must be initiated.

#### Summary of the invention

Accordingly, the object of the present invention is to mitigate the above-mentioned drawbacks and to provide a method for extracting information from a database,  
10 which method allows the user to freely select mathematical functions and incorporate calculation variables in these functions as well as to freely select classification variables for presentation of the results.

This object is achieved by a method having the  
15 features recited in independent claim 1. Preferred embodiments are recited in the dependent claims.

According to the present invention there is provided a method for generating a final data structure, i.e. a multidimensional cube, from data in a database in an  
20 efficient way, with respect to both process time and memory requirement. Since the cube can be generated much faster than in prior-art solutions, it is possible to generate multidimensional cubes *ad hoc*. The user can interactively define and generate a cube without being  
25 limited to a very small number of mathematical functions and variables. The mathematical function is normally composed of a combination of mathematical expressions. If the user needs to modify the mathematical function by changing, adding or removing a mathematical expression, a  
30 new cube can normally be generated in a time short enough not to disturb the user in his work. Similarly, if the user desires to add or remove a variable, the cube can be rapidly regenerated.

This is achieved by a clever grouping of all relevant data tables into boundary tables and connecting  
35 tables, respectively, based on the type of variables included in each table. By electing one of these tables

as a starting point and by building an appropriate conversion structure, the final data structure can be efficiently generated from the starting table by use of the conversion structure.

5        Preferably, the data records of the database are first read into the primary memory of a computer so that the data can be processed off-line. This will further reduce the time for searching the database and generating the final data structure. The database may be stored on a  
10 secondary memory or be a remotely stored database to which the computer is connected by a modem. It is to be understood that the database thus read into the primary memory may be a selected part of a larger database or a combination of two or more databases.

15        In one preferred embodiment, each different value of each data variable is assigned a binary code and the data records are stored in binary-coded form. On account of the binary coding, very rapid searches can be conducted in the data tables. Moreover, redundant information can  
20 be removed, resulting in a reduced amount of data.

      In another preferred embodiment, all boundary and connecting tables that include calculation variables with a need for frequency data, i.e. variables for which the number of duplicates of each value is necessary for  
25 correct evaluation of the mathematical function, define a subset. By electing the starting table from this subset and by including frequency data in the conversion structure, memory-efficient storage of duplicates can be achieved when building the final data structure.

30        In the conversion structure, the frequency data can be included by duplication of each value, i.e. the conversion structure will contain a link from each value of a connecting variable in the starting table to a correct number of each value of at least one corresponding  
35 selected variable in a boundary table. Alternatively, a counter may be included in the conversion structure for

each unique value of each connecting variable in the starting table.

Preferably, the boundary or connecting table having the largest number of data records is elected as starting  
5 table. This tends to minimise the amount of frequency data that must be incorporated in the conversion structure, which therefore can be built more rapidly.

In a further preferred embodiment, a virtual data record is created by reading a data record of the  
10 starting table and by using the conversion structure to convert each value of each connecting variable in this data record into a value of at least one corresponding selected variable. Thereby, the virtual data record will contain a current combination of values of the selected  
15 variables. The final data structure can be gradually built by sequentially reading data records from the starting table, by updating the content of the virtual data record based on the content of each such data record, and by evaluating the mathematical function based  
20 on the content of each such updated virtual data record. This procedure minimises the amount of computer memory that is needed for extracting the requested information from the database. Further, virtual data records containing undefined values, so-called NULL values, of any  
25 calculation variable can often be immediately removed, in particular when all calculation variables exhibit NULL-values, since in many cases such values can not be used in the evaluation of the mathematical function. This feature will contribute to an optimised performance.

30 In another preferred embodiment, an intermediate data structure is built based on the content of the virtual data record. Each data record of the intermediate data structure contains a field for each selected classification variable and an aggregation field for each  
35 mathematical expression included in the mathematical function. For each updated virtual data record, each mathematical expression is evaluated and the result is

aggregated in the appropriate aggregation field based on the current value of each selected classification variable. Such an intermediate data structure allows the user to combine mathematical expressions with different  
5 need for frequency data in one mathematical function. By building several conversion structures incorporating corresponding frequency data, and by evaluating the data records of a starting table for each such mathematical expression based on a corresponding conversion structure,  
10 it is possible to merge the results of these evaluations in one intermediate data structure. Likewise, if the user modifies the mathematical function by adding a new mathematical expression operating on the already selected calculation variables, it is only necessary to add an  
15 aggregation field to the existing intermediate data structure, or to extend an existing aggregation field.

It should be noted that the virtual data record in general is indeed virtual, i.e. it is not physically allocated any memory, during the transition from a data  
20 record of the starting table to the final data structure. However, such a virtual data record can always, at least implicitly, be identified in the procedure of converting the content of a data record of the starting table into current values of the selected variables.

#### 25 Description of preferred embodiments

The present invention will now be described by way of examples, reference being made to the tables of Appendix A and to Figs 1-2 of the drawings, Fig. 1 showing the content of a database after identification of  
30 relevant data tables according to the inventive method, and Fig. 2 showing a sequence of steps of an embodiment of the method according to the invention.

A database, as shown in Fig. 1, comprises a number of data tables (Tables 1-5). Each data table contains  
35 data values of a number of data variables. For example, in Table 1 each data record contains data values of the data variables "Product", "Price" and "Part". If there is



no specific value in a field of the data record, this field is considered to hold a NULL-value. Similarly, in Table 2 each data record contains values of the variables "Date", "Client", "Product" and "Number". Typically, the data values are stored in the form of ASCII-coded strings.

The method according to the present invention is implemented by means of a computer program. In a first step (step 101), the program reads all data records in the database, for instance using a SELECT statement which selects all the tables of the database, i.e. Tables 1-5 in this case. Typically, the database is read into the primary memory of the computer.

To increase the evaluation speed, it is preferred that each unique value of each data variable in said database is assigned a different binary code and that the data records are stored in binary-coded form (step 101). This is typically done when the program first reads the data records from the database. For each input table, the following steps are carried out. First the column names, i.e. the variables, of the table are successively read. Every time a new data variable appears, a data structure is instantiated for it. Then, an internal table structure is instantiated to contain all the data records in binary form, whereupon the data records are successively read and binary-coded. For each data value, the data structure of the corresponding data variable is checked to establish if the value has previously been assigned a binary code. If so, that binary code is inserted in the proper place in the above-mentioned table structure. If not, the data value is added to the data structure and assigned a new binary code, preferably the next one in ascending order, before being inserted in the table structure. In other words, for each data variable, a unique binary code is assigned to each unique data value.

Tables 6-12 of Appendix A show the binary codes assigned to different data values of some data variables that are included in the database of Fig. 1.

After having read all data records in the database,  
5 the program analyses the database to identify all connections between the data tables (step 102). A connection between two data tables means that these data tables have one variable in common. Different algorithms for performing such an analysis are known in the art. After the  
10 analysis all data tables are virtually connected. In Fig. 1, such virtual connections are illustrated by double-ended arrows (a). The virtually connected data tables should form at least one so-called snowflake structure, i.e. a branching data structure in which there is one and  
15 only one connecting path between any two data tables in the database. Thus, a snowflake structure does not contain any loops. If loops do occur among the virtually connected data tables, e.g. if two tables have more than one variable in common, a snowflake structure can in some  
20 cases still be formed by means of special algorithms known in the art for resolving such loops.

After this initial analysis, the user can start to explore the database. In doing so, the user defines a mathematical function, which could be a combination of  
25 mathematical expressions (step 103). Assume that the user wants to extract the total sales per year and client from the database in Fig. 1. The user defines a corresponding mathematical function "SUM(x\*y)", and selects the calculation variables to be included in this function: "Price"  
30 and "Number". The user also selects the classification variables: "Client" and "Year".

The computer program then identifies all relevant data tables (step 104), i.e. all data tables containing any one of the selected calculation and classification  
35 variables, such data tables being denoted boundary tables, as well as all intermediate data tables in the connecting path(s) between these boundary tables in the

snowflake structure, such data tables being denoted connecting tables. For the sake of clarity, the group of relevant data tables (Tables 1-3) is included in a first frame (A) in Fig. 1. Evidently, there are no connecting  
5 tables in this particular case.

In the present case, all occurrences of every value, i.e. frequency data, of the selected calculation variables must be included for evaluation of the mathematical function. In Fig. 1, the selected variables  
10 ("Price", "Number") requiring such frequency data are indicated by bold arrows (b), whereas remaining selected variables are indicated by dotted lines (b'). Now, a subset (B) can be defined that includes all boundary tables (Tables 1-2) containing such calculation variables  
15 and any connecting tables between such boundary tables in the snowflake structure. It should be noted that the frequency requirement of a particular variable is determined by the mathematical expression in which it is included. Determination of an average or a median calls  
20 for frequency information. In general, the same is true for determination of a sum, whereas determination of a maximum or a minimum does not require frequency data of the calculation variables. It can also be noted that classification variables in general do not require  
25 frequency data.

Then, a starting table is elected, preferably among the data tables within subset (B), most preferably the data table with the largest number of data records in this subset (step 105). In Fig. 1, Table 2 is elected as  
30 the starting table. Thus, the starting table contains selected variables ("Client", "Number"), and connecting variables ("Date", "Product"). These connecting variables link the starting table (Table 2) to the boundary tables (Tables 1 and 3).

35 Thereafter, a conversion structure is built (step 106), as shown in Tables 13 and 14. This conversion structure is used for translating each value of each

connecting variable ("Date", "Product") in the starting table (Table 2) into a value of a corresponding selected variable ("Year", "Price") in the boundary tables (Table 3 and 1, respectively). Table 13 is built by successively  
5 reading data records of Table 3 and creating a link between each unique value of the connecting variable ("Date") and a corresponding value of the selected variable ("Year"). It can be noted that there is no link from value 4 ("Date: 1999-01-12"), since this value is  
10 not included in the boundary table. Similarly, Table 14 is built by successively reading data records of Table 1 and creating a link between each unique value of the connecting variable ("Product") and a corresponding value of the selected variable ("Price"). In this case, value 2  
15 ("Product: Toothpaste") is linked to two values of the selected variable ("Price: 6.5"), since this connection occurs twice in the boundary table. Thus, frequency data is included in the conversion structure. Also note that there is no link from value 3 ("Product: Shampoo").

20 When the conversion structure has been built, a virtual data record is created. Such a virtual data record, as shown in Table 15, accommodates all selected variables ("Client", "Year", "Price", "Number") in the database. In building the virtual data record (step 107-  
25 108), a data record is first read from the starting table (Table 2). Then, the value of each selected variable ("Client", "Number") in the current data record of the starting table is incorporated in the virtual data record. Also, by using the conversion structure (Tables  
30 13-14) each value of each connecting variable ("Date", "Product") in the current data record of the starting table is converted into a value of a corresponding selected variable ("Year", "Price"), this value also being incorporated in the virtual data record.

35 At this stage (step 109), the virtual data record is used to build an intermediate data structure (Table 16). Each data record of the intermediate data structure

accommodates each selected classification variable (dimension) and an aggregation field for each mathematical expression implied by the mathematical function. The intermediate data structure (Table 16) is built based on the values of the selected variables in the virtual data record. Thus, each mathematical expression is evaluated based on one or more values of one or more relevant calculation variables in the virtual data record, and the result is aggregated in the appropriate aggregation field based on the combination of current values of the classification variables ("Client", "Year").

The above procedure is repeated for all data records of the starting table (step 110). Thus, an intermediate data structure is built by successively reading data records of the starting table, by incorporating the current values of the selected variables in a virtual data record, and by evaluating each mathematical expression based on the content of the virtual data record. If the current combination of values of classification variables in the virtual data record is new, a new data record is created in the intermediate data structure to hold the result of the evaluation. Otherwise, the appropriate data record is rapidly found, and the result of the evaluation is aggregated in the aggregation field. Thus, data records are added to the intermediate data structure as the starting table is traversed. Preferably, the intermediate data structure is a data table associated with an efficient index system, such as an AVL or a hash structure. In most cases, the aggregation field is implemented as a summation register, in which the result of the evaluated mathematical expression is accumulated. In some cases, e.g. when evaluating a median, the aggregation field is instead implemented to hold all individual results for a unique combination of values of the specified classification variables. It should be noted that only one virtual data record is needed in the procedure of building the intermediate data structure

from the starting table. Thus, the content of the virtual data record is updated for each data record of the starting table. This will minimise the memory requirement in executing the computer program.

5       The procedure of building the intermediate data structure will be further described with reference to Tables 15-16. In creating the first virtual data record R1, as shown in Table 15, the values of the selected variables "Client" and "Number" are directly taken from  
10 the first data record of the starting table (Table 2). Then, the value "1999-01-02" of the connecting variable "Date" is transferred into the value "1999" of the selected variable "Year", by means of the conversion structure (Table 13). Similarly, the value "Toothpaste"  
15 of the connecting variable "Product" is transferred into the value "6.5" of the selected variable "Price" by means of the conversion structure (Table 14), thereby forming the virtual data record R1. Then, a data record is created in the intermediate data structure, as shown in  
20 Table 16. In this case, the intermediate data structure has tree columns, two of which holds selected classification variables ("Client", "Year"). The third column holds an aggregation field, in which the evaluated result of the mathematical expression ("x\*y") operating on the  
25 selected calculation variables ("Number", "Price") is aggregated. In evaluating virtual data record R1, the current values (binary codes: 0,0) of the classification variables are first read and incorporated in this data record of the intermediate data structure. Then, the  
30 current values (binary codes: 2,0) of the calculation variables are read. The mathematical expression is evaluated for these values and added to the associated aggregation field.

Next, the virtual data record is updated based on  
35 the starting table. Since the conversion structure (Table 14) indicates a duplicate of the value "6.5" of the selected variable "Price" for the value "Toothpaste" of

the connecting variable "Product", the updated virtual data record R2 is unchanged and identical to R1. Then, the virtual data record R2 is evaluated as described above. In this case, the intermediate data structure contains a data record corresponding to the current values (binary codes: 0,0) of the classification variables. Thus, the evaluated result of the mathematical expression is accumulated in the associated aggregation field.

Next, the virtual data record is updated based on the second data record of starting table. In evaluating this updated virtual data record R3, a new data record is created in the intermediate data structure, and so on.

It should be noted that NULL values are represented by a binary code of -2 in this example. In the illustrated example, it should also be noted that any virtual data records holding a NULL value (-2) of any one of the calculation variables can be directly eliminated, since NULL values can not be evaluated in the mathematical expression ("x\*y"). It should also be noted that all NULL values (-2) of the classification variables are treated as any other valid value and are placed in the intermediate data structure.

After traversing the starting table, the intermediate data structure contains four data records, each including a unique combination of values (0,0; 1,0; 2,0; 3,-2) of the classification variables, and the corresponding accumulated result (41; 37.5; 60; 75) of the evaluated mathematical expression.

Preferably, the intermediate data structure is also processed to eliminate one or more classification variables (dimensions). Preferably, this is done during the process of building the intermediate data structure, as described above. Every time a virtual data record is evaluated, additional data records are created, or found if they already exist, in the intermediate data structure. Each of these additional data records is destined to hold an aggregation of the evaluated result of the

mathematical expression for all values of one or more classification variables. Thus, when the starting table has been traversed, the intermediate data structure will contain both the aggregated results for all unique  
5 combinations of values of the classification variables, and the aggregated results after elimination of each relevant classification variable.

This procedure of eliminating dimensions in the intermediate data structure will be further described  
10 with reference to Tables 15 and 16. When virtual data record R1 is evaluated (Table 15) and the first data record (0,0) is created in the intermediate data structure, additional data records are created in this structure. Such additional data records are destined to hold  
15 the corresponding results when one or more dimensions are eliminated. In Table 16, a classification variable is assigned a binary code of -1 in the intermediate data structure to denote that all values of this variable are evaluated. In this case, three additional data records  
20 are created, each holding a new combination of values (-1,0; 0,-1; -1,-1) of the classification variables. The evaluated result is aggregated in the associated aggregation field of these additional data records. The first (-1,0) of these additional data records is destined to  
25 hold the aggregated result for all values of the classification variable "Client" when the classification variable "Year" has the value "1999". The second (0,-1) additional data record is destined to hold the aggregated result for all values of the classification variable  
30 "Year" when the classification variable "Client" is "Nisse". The third (-1,-1) additional data record is destined to hold the aggregated result for all values of both classification variables "Client" and "Year".

When virtual data record R2 is evaluated, the result  
35 is aggregated in the aggregation field associated with the current combination of values (binary codes: 0,0) of the classification variables, as well as in the aggre-



gation fields associated with relevant additional data records (binary codes: -1,0; 0,-1; -1,-1). When virtual data record R3 is evaluated, the result is aggregated in the aggregation field associated with the current combination of values (binary codes: 1,0) of the classification variables. The result is also aggregated in the aggregation field of a newly created additional data record (binary codes: 1,-1) and in the aggregation fields associated with relevant existing data records (binary codes: -1,0; -1,-1) in the intermediate data structure.

After traversing the starting table, the intermediate data structure contains eleven data records, as shown in Table 16.

Preferably, if the intermediate data structure accommodates more than two classification variables, the intermediate data structure will, for each eliminated classification variable, contain the evaluated results aggregated over all values of this classification variable for each unique combination of values of remaining classification variables.

When the intermediate data structure has been built, a final data structure, i.e. a multidimensional cube, as shown in non-binary notation in Table 17, is created by evaluating the mathematical function ("SUM(x\*y)") based on the results of the mathematical expression ("x\*y") contained in the intermediate data structure (step 111). In doing so, the results in the aggregation fields for each unique combination of values of the classification variables are combined. In the illustrated case, the creation of the final data structure is straightforward, due to the trivial nature of the present mathematical function. The content of the final data structure might then (step 112) be presented to the user in a two-dimensional table, as shown in Table 18. Alternatively, if the final data structure contains many dimensions, the data can be presented in a pivot table, in which the user

interactively can move up and down in dimensions, as is well known in the art.

Below, a second example of the inventive method is described with reference to Tables 20-29. The description will only elaborate on certain aspects of this example, namely building a conversion structure including data from connecting tables, and building an intermediate data structure for a more complicated mathematical function. In this example, the user wants to extract sales data per client from a database, which contains the data tables shown in Tables 20-23. For ease of interpretation, the binary coding is omitted in this example.

The user has specified the following mathematical functions, for which the result should be partitioned per Client:

- a) "IF(Only(Environment index)='I') THEN Sum(Number\*Price)\*2, ELSE Sum(Number\*Price))", and
- b) "Avg(Number\*Price)"

The mathematical function (a) specifies that the sales figures should be doubled for products that belong to a product group having an environment index of 'I', while the actual sales figures should be used for other products. The mathematical function (b) has been included for reference.

In this case, the selected classification variables are "Environment index" and "Client", and the selected calculation variables are "Number" and "Price". Tables 20, 22 and 23 are identified as boundary tables, whereas Table 21 is identified as a connecting table. Table 20 is elected as starting table. Thus, the starting table contains selected variables ("Number", "Client"), and a connecting variable ("Product"). The connecting variable links the starting table (Table 20) to the boundary tables (Tables 22-23), via the connecting table (Table 21).

Next, the formation of the conversion structure will be described with reference to Tables 24-26. A first part

(Table 24) of the conversion structure is built by successively reading data records of a first boundary table (Table 23) and creating a link between each unique value of the connecting variable ("Product group") and a corresponding value of the selected variable ("Environment index"). Similarly, a second part (Table 25) of the conversion structure is built by successively reading data records of a second boundary table (Table 22) and creating a link between each unique value of the connecting variable ("Price group") and a corresponding value of the selected variable ("Price"). Then, data records of the connecting table (Table 21) is read successively. Each value of the connecting variables ("Product group" and "Price group", respectively) in Tables 24 and 25 is substituted for a corresponding value of a connecting variable ("Product") in Table 21. The result is merged in one final conversion structure, as shown in Table 26.

Then, an intermediate data structure is built by successively reading data records of the starting table (Table 20), by using the conversion structure (Table 26) to incorporate the current values of the selected variables ("Environment index", "Client", "Number", "Price") in the virtual data record, and by evaluating each mathematical expression based on the current content of the virtual data record.

For reasons of clarity, Table 27 displays the corresponding content of the virtual data record for each data record of the starting table. As noted in connection with the first example, only one virtual data record is needed. The content of this virtual data record is updated, i.e. replaced, for each data record of the starting table.

Each data record of the intermediate data structure, as shown in Table 28, accommodates a value of each selected classification variable ("Client", "Environment index") and an aggregation field for each mathematical expression implied by the mathematical functions. In this

case, the intermediate data structure contains two aggregation fields. One aggregation field contains the aggregated result of the mathematical expression ("x\*y") operating on the selected calculation variables

5 ("Number", "Price"), as well as a counter of the number of such operations. The layout of this aggregation field is given by the fact that an average quantity should be calculated ("Avg(x\*y)"). The other aggregation field is designed to hold the lowest and highest values of the  
10 classification variable "Environment index" for each combination of values of the classification variables.

As in the first example, the intermediate data structure (Table 28) is built by evaluating the mathematical expression for the current content of the  
15 virtual data record (each row in Table 27), and by aggregating the result in the appropriate aggregation field based on the combination of current values of the classification variables ("Client", "Environment index"). The intermediate data structure also includes data  
20 records in which the value "<ALL>" has been assigned to one or both of the classification variables. The corresponding aggregation fields contain the aggregated result when the one or more classification variables (dimensions) are eliminated.

25 When the intermediate data structure has been built, a final data structure, i.e. a multidimensional cube, is created by evaluating the mathematical functions based on the evaluated results of the mathematical expressions contained in the intermediate data structure. Each data  
30 record of the final data structure, as shown in Table 29, accommodates a value of each selected classification variable ("Client", "Environment index") and an aggregation field for each mathematical function selected by the user.

35 The final data structure is built based on the results in the aggregation fields of the intermediate data structure for each unique combination of values of

the classification variables. When function (a) is evaluated, by sequentially reading data records of Table 28, the program first checks if both values in the last column of Table 28 is equal to 'I'. If so, the relevant result contained in the first aggregation field of Table 28 is multiplied by two and stored in Table 29. If not, the relevant result contained in the first aggregation field of Table 28 is directly stored in Table 29. When function (b) is evaluated, the aggregated result of the mathematical expression ("x\*y") operating on the selected calculation variables ("Number", "Price") is divided by the number of such operations, both of which are stored in the first aggregation field of Table 28. The result is stored in the second aggregation field of Table 29.

Evidently, the present invention allows the user to freely select mathematical functions and incorporate calculation variables in these functions as well as to freely select classification variables for presentation of the results.

As an alternative, albeit less memory-efficient, to the illustrated procedure of building an intermediate data structure based on sequential data records from the starting table, it is conceivable to first build a so-called join table. This join table is built by traversing all data records of the starting table and, by use of the conversion structure, converting each value of each connecting variable in the starting table into a value of at least one corresponding selected variable in a boundary table. Thus, the data records of the join table will contain all occurring combinations of values of the selected variables. Then, the intermediate data structure is built based on the content of the join table. For each record of the join table, each mathematical expression is evaluated and the result is aggregated in the appropriate aggregation field based on the current value of each selected classification variable. However, this alter-

native procedure requires more computer memory to extract the requested information.

It should be realised that the mathematical function could contain mathematical expressions having different, and conflicting, needs for frequency data. In this case, steps 104-110 (Fig. 2) are repeated for each such mathematical expression, and the results are stored in one common intermediate data structure. Alternatively, one final data structure, i.e. multidimensional cube, could be built for each mathematical expression, the contents of these cubes being fused during presentation to the user.

Appendix ATable 6

<b>Product</b>	
<b>Soap</b>	<b>0</b>
<b>Soft soap</b>	<b>1</b>
<b>Toothpaste</b>	<b>2</b>
<b>Shampoo</b>	<b>3</b>

Table 8

<b>Date</b>	
<b>1999-01-02</b>	<b>0</b>
<b>1999-01-07</b>	<b>1</b>
<b>1999-01-08</b>	<b>2</b>
<b>1999-01-11</b>	<b>3</b>
<b>1999-01-12</b>	<b>4</b>
<b>1999-01-15</b>	<b>5</b>

Table 10

<b>Number</b>	
<b>3</b>	<b>0</b>
<b>5</b>	<b>1</b>
<b>8</b>	<b>2</b>
<b>2</b>	<b>3</b>
<b>10</b>	<b>4</b>

Table 7

<b>Price</b>	
<b>7.5</b>	<b>0</b>
<b>9.35</b>	<b>1</b>
<b>6.5</b>	<b>2</b>

Table 9

<b>Client</b>	
<b>Nisse</b>	<b>0</b>
<b>Gullan</b>	<b>1</b>
<b>Kalle</b>	<b>2</b>
<b>Pekka</b>	<b>3</b>
<b>Jens</b>	<b>4</b>

Table 11

<b>Year</b>	
<b>1999</b>	<b>0</b>

Table 12

<b>Country</b>	
<b>Sweden</b>	<b>0</b>
<b>Denmark</b>	<b>1</b>
<b>Finland</b>	<b>2</b>

Table 13

0	→	0
1	→	0
2	→	0
3	→	0
5	→	0

Table 14**Product → Price**

0	→	0
1	→	1
2	→	22

Table 15Table 16Aggregation field

Client	Year	Price	Number	Client	Year	$\Sigma$ Number*Price
0			0			
0	0		0			
R1	0	0	2	0	0	Sum = Sum (0) + 3 x 6.5 -> 20.5
R2	0	0	2	0	0	Sum = Sum (20.5) + 3 x 6.5 -> 41
R3	1	0	0	1	0	Sum = Sum (0) + 5 x 7.5 -> 37.5
R4	2	0	0	2	0	Sum = Sum (0) + 8 x 7.5 -> 60
R5	2	0	-2	3	0	Sum = Sum (60) + 2 x (NULL) -> 60
R6	3	-2	0	4	-2	Sum = Sum (0) + 10 x 7.5 -> 75
R7	0	0	0	3	0	Sum = Sum (41) + 2 x (NULL) -> 41
				-1	0	Sum = Sum (0) + 20.5 + 20.5 + 37.5 + 60 + 0 + 0 -> 138.5
				-1	-2	Sum = Sum (0) + 75 -> 75
				0	-1	Sum = Sum (0) + 20.5 + 20.5 + 0 -> 41
				1	-1	Sum = Sum (0) + 37.5 -> 37.5
				2	-1	Sum = Sum (0) + 60 + 0 -> 60
				3	-1	Sum = Sum (0) + 75 -> 75
				-1	-1	Sum = Sum (0) + 20.5 + 20.5 + 37.5 + 60 + 0 + 75 + 0 -> 213.5



**Table 17**

<i>Client</i>	<i>Year</i>	<i>Sum (Number x Price)</i>
Nisse	1999	41
Gullan	1999	37.5
Kalle	1999	60
Pekka	<NULL>	75
<ALL>	1999	138.5
<ALL>	<NULL>	75
Nisse	<ALL>	41
Gullan	<ALL>	37.5
Kalle	<ALL>	60
Pekka	<ALL>	75
<ALLA	<ALL>	213.5

**Table 18***Sum (Price\*Number) Per Client, Year*

	1999	<NULL>	<ALL>
Nisse	41		41
Gullan	37.5		37.5
Kalle	60		60
Pekka		75	75
<ALL>	138.5	75	75

**Table 20**

<i>Date</i>	<i>Product</i>	<i>Number</i>	<i>Client</i>
1998-12 -20	B	5	Nisse
1999-02-05	A	7	Kalle
1999-02-06	B	9	Kalle

**Table 21**

<i>Product</i>	<i>Price group</i>	<i>Product group</i>
A	4	Z
B	3	X

**Table 22**

<i>Price group</i>	<i>Price</i>
3	5.5
4	3.5

**Table 23**

<i>Product group</i>	<i>Environment index</i>	<i>Legal status</i>
X	I	YES
Y	IX	NO
Z	II	YES

**Table 24****Product group->Environment index**

X → I  
 Y → IX  
 Z → II

**Table 25****Price group ->Price**

3 → 5.5  
 4 → 3.5

**Table 26****Product->Price, Environment index**

A → 3.5,II  
 B → 5.5,I

**Table 27**

<b>Client</b>	<b>Environment index</b>	<b>Number</b>	<b>Price</b>
Nisse	I	5	5.5
Kalle	II	7	3.5
Kalle	I	9	5.5

**Table 28**

<b>Client</b>	<b>Environment index</b>	<b><math>\Sigma</math>-Number x Price</b>	<b><math>\Sigma</math>-Environment index</b>
Nisse	I	$\Sigma x$ : 27.5, N: 1	First: I, Last: I
Kalle	II	$\Sigma x$ : 24.5, N: 1	First: II, Last: II
Kalle	I	$\Sigma x$ : 49.5, N: 1	First: I, Last: I
<ALL>	I	$\Sigma x$ : 77, N: 2	First: I, Last: I
<ALL>	II	$\Sigma x$ : 24.5, N: 1	First: II, Last: II
<ALL>	<ALL>	$\Sigma x$ : 101.5, N: 3	First: I, Last: II

**Table 29**

<b>Client</b>	<b>Environment index</b>	<b>IF (Only (Environment index)='I', Sum(Number*Price)*2,Sum(Number*Price))</b>	<b>Avg(Number*Price)</b>
Nisse	I	55.0	27.5
Kalle	II	24.5	24.5
Kalle	I	99.0	49.5
<ALLA>	I	154.0	38.5
<ALLA>	II	24.5	24.5
<ALLA>	<ALL>	<NULL>	33.8

## CLAIMS

1. A method for extracting information from a  
5 database, which comprises a number of data tables  
containing values of a number of variables, each data  
table consisting of at least one data record including at  
least two of said values, said information being  
extracted by evaluation of at least one mathematical  
10 function operating on one or more selected calculation  
variables, said extracted information being partitioned  
on one or more selected classification variables,  
c h a r a c t e r i s e d by the steps of:

identifying all data tables containing at least one  
15 value of one of said selected variables, such data tables  
being boundary tables;

identifying all data tables that, directly or  
indirectly, have variables in common with said boundary  
tables and connect the same, such data tables being  
20 connecting tables;

electing a starting table among said boundary and  
connecting tables;

building a conversion structure that links values of  
each selected variable in said boundary tables to  
25 corresponding values of one or more connecting variables  
in said starting table; and

evaluating said mathematical function for each data  
record of said starting table, by using said conversion  
structure to convert each value of each connecting  
30 variable into at least one value of at least one  
corresponding selected variable, such that said  
evaluation yields a final data structure containing a  
result of said mathematical function for every unique  
value of each classification variable.

35 2. A method as set forth in claim 1, c h a r a c -  
t e r i s e d by the further step of presenting relevant

parts of said resulting data structure to the user in human-readable form.

3. A method as set forth in claim 1 or 2, characterised by the further step of initially  
5 reading said data records of said database into the primary memory of a computer.

4. A method as set forth in any one of the preceding claims, characterised by the further step of initially assigning a different binary code to each  
10 unique value of each data variable in said database and storing the data records in binary-coded form.

5. A method as set forth in any one of the preceding claims, characterised by the further steps of initially identifying all data tables in said database  
15 that have variables in common, and assigning virtual connections between such data tables, thereby creating a database with a snowflake structure, wherein said connecting tables are located between said boundary tables in said snowflake structure.

20 6. A method as set forth in any one of the preceding claims, characterised by the further steps of identifying all calculation variables for which the number of occurrences of each value is necessary for correct evaluation of said mathematical function,  
25 defining a subset of data tables consisting of boundary tables containing such variables and data tables connecting such boundary tables, electing said starting table from said subset, and including data on said number of occurrences of each value in said conversion  
30 structure.

7. A method as set forth in any one of the preceding claims, characterised in that said starting table is the data table among said boundary and connecting tables having the largest number of data  
35 records.

8. A method as set forth in any one of the preceding claims, characterised by the further step of

building said final data structure, which includes a number of data records, each of which contains a field for each selected classification variable and an aggregation field for said mathematical function, wherein  
5 said building step includes sequentially reading a data record of said starting table, creating a current combination of values of said selected variables by using said conversion structure to convert each value of each connecting variable in said data record into a value of  
10 at least one corresponding selected variable, evaluating said mathematical function for said current combination of values, and aggregating the result of said evaluation in the appropriate aggregation field based on the current value of each selected classification variable.

15 9. A method as set forth in any one of claims 1-7, characterised by the further step of creating a virtual data record containing a combination of values of said selected variables, wherein said creating step includes reading a data record of said starting table and  
20 using said conversion structure to convert each value of each connecting variable in said data record into a value of at least one corresponding selected variable.

10. A method as set forth in claim 9, characterised by the further step of building said final  
25 data structure which includes a number of data records, each of which contains a field for each selected classification variable and an aggregation field for said mathematical function, wherein said building step includes sequentially reading a data record of said  
30 starting table, updating the content of said virtual data record based on the content of each such data record, evaluating said mathematical function based on said updated virtual data record, and aggregating the result of said evaluation in the appropriate aggregation field  
35 based on the current value of each selected classification variable in said updated virtual data record.

11. A method as set forth in claim 9, c h a r a c -  
t e r i s e d by the further step of building an  
intermediate data structure which includes a number of  
data records, each of which contains a field for each  
5 selected classification variable and an aggregation field  
for each mathematical expression implied by said  
mathematical function, wherein said building step  
includes sequentially reading a data record of said  
starting table, updating the content of said virtual data  
10 record based on the content of each such data record,  
evaluating each mathematical expression based on said  
updated virtual data record, and aggregating the result  
of said evaluation in an appropriate aggregation field  
based on the current value of each selected  
15 classification variable in said updated virtual data  
record.

12. A method as set forth in claim 11, c h a r a c -  
t e r i s e d in that said step of building said  
intermediate data structure includes:  
20 eliminating one of said classification variables in  
said intermediate data structure by aggregating said  
results over all values of said one classification  
variable for each unique combination of values of  
remaining classification variables, by creating  
25 additional data records, and by incorporating said  
aggregated results in said additional data records of  
said intermediate data structure.

13. A method as set forth in claim 11 or 12, c h a -  
r a c t e r i s e d by the further step of evaluating said  
30 mathematical function based on said results in said  
aggregation fields for each unique combination of values  
of said classification variables, thereby building said  
final data structure.

14. A method as set forth in any one of the  
35 preceding claims, c h a r a c t e r i s e d in that said  
step of building said conversion structure includes:

a) reading data records of a boundary table, and creating a conversion structure including a link between each unique value of at least one connecting variable in said boundary table and each corresponding value of at least one selected variable therein;


b) moving from said boundary table towards said starting table;

c) if a connecting table is found, reading data records of said connecting table, and substituting each unique value of said at least one connecting variable in said conversion structure for at least one corresponding unique value of at least one connecting variable in said connecting table; and

d) repeating steps (b)-(c) until said starting table is found.


15. An article of manufacture comprising a computer-readable medium having stored thereon a computer program for effecting the steps of a method for extracting information from a database as set forth in any one of the preceding claims.

1/2

**Sum(Price\*Number) per Client, Year****Fig. 1**



2/2

**Fig. 2**

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 00/00482

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: G06F 17/30

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5517641 A (R.E. BARRY ET AL.), 14 May 1996 (14.05.96), figure 8, abstract --	1-15
A	US 5842209 A (D.J. MOCEK ET AL.), 24 November 1998 (24.11.98), figure 4, abstract --	1-15
A	US 5423035 A (D. DEPREZ), 6 June 1995 (06.06.95), figure 1, abstract --	1-15
P,A	US 5960428 A (B.G. LINDSAY ET AL.), 28 Sept 1999 (28.09.99), figure 4, abstract -- -----	1-15

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

## \* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

2 August 2000

03 -08- 2000

Name and mailing address of the ISA/  
Swedish Patent Office  
Box 5055, S-102 42 STOCKHOLM  
Facsimile No. +46 8 666 02 86

Authorized officer

Patrik Blidefalk/AE  
Telephone No. +46 8 782 25 00

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

02/12/99

International application No.  
PCT/SE 00/00482

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5517641 A	14/05/96	US 5758357 A	26/05/98
		US 5887274 A	23/03/99
		US 5408654 A	18/04/95
US 5842209 A	24/11/98	NONE	
US 5423035 A	06/06/95	NONE	
US 5960428 A	28/09/99	NONE	

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**